

RoHS Compliant

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:500M ohm min.




Withstanding Voltage:500V AC/Minute

Ordering Information


12751S-XXX072-NX

1 2 3 4 5

- 1:— Series No.
2:— S: Straight Type
3:— No. of Positions
4:— A: Gold Flash
H: Selective Gold Plated
Q: Tin Plated
5:— A: In bag
B: Tube
C: Tray



Recommended PCB Layout

				DR.BY.: Kenry		GENERAL TOLERANCE:		PART NO : 12751S-XXX072-NX		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED							
				CHKD.: Tony		LINEAR		ANGLES						DWG. NO.:			
						X.: ±0.30		X': ±5.0°		TITLE : 1.27mm Pitch Pin Header Straight Type		SHEET: 1/1				A4	
1X				ORIGINAL		Kenry						SCALE: 1:1					
REV.				DESCRIPTION		DR.BY		ECN. NO.		APPD.: Billy		UNIT: mm					
						X.XX: ±0.15		X.XX': ±2.0°									
						X.XXX: ±0.10		X.XXX': ±1.0°		DATE: 20-Nov-2014							