

Specifications:**Material And Finish:**

Insulator:High Temp. Plastic(LCP UL94V-0)

Insulator Color:Black

Contact:Phosphor Bronze

Body lock:Brass

Plated:Gold Plating on Contact and Tin Plating
on Solder tail, over nickel Plating**Rating:**

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:30m Ohm Max






Insulator resistance:1000M ohm min.

Withstanding Voltage:750V AC/Minute

Ordering Information**ATABSS-22X-01-X**

1 2 3 4 5

- 1: — Series No.
2: — S:Striaight type
3: — No. of Positions
4: — H:Selective Gold Plated
K:Selective Gold 5U"
L:Selective Gold 10U"
M:Selective Gold 15U"
P:Selective Gold 30U"
5: — B:In Tube
E:W/Cap In Tube



5X				DR.BY.: Samson	GENERAL TOLERANCE:	PART NO : ATABSS-22X-01-X	HJBRIGHT 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED	
4X				CHKD.: Tony	LINEAR ANGLES	DWG. NO.: RD0805-028		
3X				APPD.: Billy	X.: ±0.30 X': ±5.0°	TITLE : SATA 7+15P Female Striaight type	SHEET: 1/1	A4
2X					X.X: ±0.20 X.X': ±3.0°	DATE: 07-May-2008	SCALE: 1:1	
1X	ORIGINAL	Samson			X.XX: ±0.15 X.XX': ±2.0°		UNIT: mm	
REV.	DESCRIPTION	DR.BY	ECN. NO.		X.XXX: ±0.10 X.XXX': ±1.0°			