




Plated: See Ordering Information

Operating Temperature Range: $-40^{\circ}\sim+105^{\circ}\text{C}$


Withstanding Voltage:500V AC/Minute

$$\overline{1} \quad \overline{2} \quad \overline{3} \quad \overline{4} \quad \overline{5}$$

- 1:— Series No.
2:— S:Straight Type
3:— No. of Positions(01-40)
4:— A:Gold Flash
H:Selective Gold Plated
Q:Tin Plated
5:— A:In bag
B:Tube



Recommended PCB Layout



5X				DR.BY.: Aaron	GENERAL TOLERANCE:		PART NO : 200212S-XXXXXX-NX		HJBRIGHT[®] 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X					LINEAR	ANGLES	DWG. NO.:					
3X				CHKD.: Tony	x.: ±0.30	x°: ±5.0°	TITLE : 2.0mm Pitch Pin Header Straight Type		SHEET: 1/1			A4
2X					x.x: ±0.20	x.x°: ±3.0°			SCALE: 1:1			
1X	ORIGINAL	Aaron		APPD.: Billy	x.xx: ±0.15	x.xx°: ±2.0°	DATE: 07-May-2017		UNIT: mm			
REV.	DESCRIPTION	DR.BY	ECN. NO.		x.xxx: ±0.10	x.xxx°: ±1.0°						