

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:1000M ohm min.





Withstanding Voltage:500V AC/Minute

Ordering Information

200522S-XXXXXX-NX

1 2 3 4 5

- 1: — Series No.
2: — S: Straight Type
3: — No. of Positions
4: — A: Gold Flash
H: Selective Gold Plated
Q: Tin Plated
5: — A: In bag
B: Tube
C: Tray



Recommended PCB Layout

5X				DR.BY:.	GENERAL TOLERANCE:		PART NO : 200522S-XXXXXX-NX	HJBRIGHT 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			 THIRD ANGLE PROJECTION	A4
4X				joy chen	LINEAR	ANGLES	DWG. NO.: RD0807-236					
3X				CHKD:.	x.: ±0.30	x': ±5.0°	TITLE : 2.0mm Pitch Pin Header Straight Type					
2X				Tony	x.x: ±0.20	x.x': ±3.0°						
1X	ORIGINAL	joy chen		APPD:.	x.xx: ±0.15	x.xx': ±2.0°						
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 23-Jul-2008	UNIT: mm	SCALE: 1:1			