

RoHS Compliant

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT+GF(UL94V-0)	BLACK	1
2	TERMINAL	PHOSPHOR BRONZE 0.15	GOLD PLATED OVER NICKEL	PINS
3	COVER	PBT+GF(UL94V-0)	BLACK	1

Ordering Information
CS1272-XXA-01-PC
1 2 3 4 5

- 1: — Series No.
2: — No. of Positions
3: — A:Gold Flash
4: — P:PBT
5: — C:In Tray

NUMBER OF POSITIONS	DIMENSION	
	A	B
06	8.00	2.54
08	9.27	3.81
10	10.54	5.08
12	11.81	6.35
14	13.08	7.62
16	14.35	8.89
20	16.89	11.43
24	19.43	13.97
26	20.70	15.24
30	23.24	17.78
34	25.78	20.32
36	27.05	21.59
40	29.59	24.13
44	32.13	26.67
50	35.94	30.48
60	42.29	36.83
64	44.83	39.37
66	46.10	40.64
68	47.37	41.91
70	48.64	43.18
74	51.18	45.72
76	52.45	46.99
80	54.99	49.53

Specifications:**Rating:**

Current Rating:1.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:100M ohm min.

Withstanding Voltage:500V AC/Minute

5X			
4X			
3X			
2X			
1X	ORIGINAL	Samson	
REV.	DESCRIPTION	DR.BY	ECN. NO.

DR.BY.: Samson
CHKD.: Tony
APPD.: Billy

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.38	X': ±5.0°
X.X: ±0.30	X.X': ±3.0°
X.XX: ±0.25	X.XX': ±2.0°
X.XXX: ±0.10	X.XXX': ±1.0°


PART NO : CS1272-XXA-01-PC
DWG. NO.:
TITLE : IDC SOCKET 1.27*1.27(二件式)
DATE: 23-Apr-2014

HJBRIGHT 东莞市华晶电子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1

SCALE:1:1

UNIT:mm



THIRD ANGLE PROJECTION

A4