

Specifications:**Material And Finish:**

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:30m Ohm Max



Insulator resistance:3000M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information**B2001M-XXX-02-1X**

1 2 3 4 5

- 1: — Series No.
2: — M:SMT Type
3: — No. of Positions
4: — A:Gold Flash
H:Selective Gold Plated
Q:Tin Plated
6: — A:In bag
B:In Tube
F:W/Cap In Tape&Reel



Recommended PCB Layout

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : B2001M-XXX-02-1X		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHE-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Samson	LINEAR	ANGLES	DWG. NO.:				
3X				CHKD.:	x.: ±0.30	x': ±5.0°	TITLE : 2.0mm Pitch Box Header SMT Type帶柱,抽第9PIN				
2X				Tony	x.x: ±0.20	x.x': ±3.0°					
1X	ORIGINAL	Samson		APPD.:	x.xx: ±0.15	x.xx': ±2.0°	DATE: 27-Nov-2013		SHEET: 1/1		A4
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx': ±1.0°			SCALE: 1:1		
							UNIT: mm	THIRD ANGLE PROJECTION			