Specifications:
Material And Finish:
Insulator:PA6T UL94V-0 Color:Black
Contact:Brass
Plated:See Ordering Information

Rating:
Current Rating:2.0 Amp
Voltage Rating:150V AC/DC
Operating Temperature Range:-40°~+105°C

Electrical:
Contact resistance:30m Ohm Max
Insulator resistance:1000M ohm min.
Withstanding Voltage:500V AC/Minute





Ordering Information
B2001S2-XXX-XX-NX
1 2 3 4 5 6

1: —— Series No.
2: —— S:Straight Type
3: —— No. of Positions
4: —— A:Gold Flash
H:Selective Gold Plated
W:Gold 5u"
Q:Tin Plated
5: —— 01:24.62
02:28.62
03:21.2mm
6: —— A:In bag
B:In Tube
C:In Tray



Recommended PCB Layout

RoHS Compliant

REV.	DESCRIPTION	DR.BY	ECN. NO.
5X			
4X			
3X			
2X			
1X	ORIGINAL	Tsw	

DR.BY.: Tsw
CHKD.: Tony
APPD.: Billy

GENERAL TOLERANCE:			
LINEAR		ANGLES	
X.:	±0.30	X°:	±5.0°
X.X:	±0.25	X.X°:	±3.0°
X.XX:	±0.15	X.XX°:	±2.0°
X.XXX:	±0.10	X.XXX°:	±1.0°

PART NO : B2001S2-XXX-XX-NX
DWG. NO.:
TITLE : 2.0mm Pitch Box Header Straight Type
DATE: 22-JUL-2020

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHE-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm
THIRD ANGLE PROJECTION
A4