

Specifications:**Material And Finish:**

Insulator:PA6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:30m Ohm Max





Insulator resistance:1000M ohm min.

Withstanding Voltage:500V AC/Minute


Ordering Information**B2002R-XXA-02-NC**

1 2 3 4 5

- 1: — Series No.
2: — R/R/A Type
3: — No. of Positions
4: — A:Gold Flash
5: — C:In Tray



Recommended PCB Layout

5X				DR.BY.: Aaron	GENERAL TOLERANCE:		PART NO : B2002R-XXA-02-NC	HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X					LINEAR	ANGLES	DWG. NO.:				
3X				CHKD.: Tony	x.: ±0.30	x': ±5.0°	TITLE : 2.0mm Pitch Box Header R/A Type	SHEET: 1/1			A4
2X					x.x: ±0.25	x.x': ±3.0°		SCALE: 1:1			
1X	ORIGINAL	Aaron		APPD.: Billy	x.xx: ±0.15	x.xx': ±2.0°		UNIT: mm			
REV.	DESCRIPTION	DR.BY	ECN. NO.		x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 25-Apr-2019				