

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Phosphor Bronze

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40° ~+105° C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:500M ohm min.





Withstanding Voltage:500V AC/Minute

Ordering Information


S12722M-XXX43-4X-G

1 2 3 4 5

- 1:— Series No.
2:— M:SMT Type
3:— No. of Positions
4:— A:Gold FlashA:Gold Flash
H:Selective Gold Plated
T:10u" Gold on contact;Matte Tin on tail
Q:Tin Plated
5:— A:In bag
B:In Tube
C:In Tray
F:W/Cap In Tape&Reel



Recommended PCB Layout(Tolerance:0.05mm)

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : S12722M-XXX43-4X-G		HJBRIGHT 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X				Samson	LINEAR	ANGLES	DWG. NO.:					
3X				CHKD.:	x.: ±0.30	x': ±5.0°	TITLE : 1.27mm Pitch PCB Socket Header SMT Type		SHEET: 1/1			A4
2X				Tony	x.x: ±0.25	x.x': ±3.0°			SCALE:1:1			
1X	ORIGINAL	Samson		APPD.:	x.xx: ±0.15	x.xx': ±2.0°	DATE: 20-Jan-2015		UNIT:mm			
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx:	x.xxx': ±1.0°						