

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:white

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:3.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information

25011R-XXX106-NX

1 2 3 4 5

1:—Series No.

2:—R/R/A Type

3:—No. of Positions





4:—A:Gold Flash

Q:Tin Plated


5:—A:In bag

B:In Tube

C:In Tray



Recommended PCB Layout

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : 25011R-XXX106-NX	HJBRIGHT® 东莞市華晶电子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		SHEET: 1/1		A4
4X				Samson	LINEAR	ANGLES	DWG. NO.:					
3X				CHKD.:	X.: ±0.30	X': ±5.0°	TITLE :	2.50mm Pitch Pin Header R/A Type		SCALE: 1:1	THIRD ANGLE PROJECTION	
2X				Tony	X.X: ±0.20	X.X': ±3.0°	DATE: 10-Dec-2013			UNIT: mm		
1X	ORIGINAL	Samson		APPD.:	X.XX: ±0.15	X.XX': ±2.0°						
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	X.XXX: ±0.10	X.XXX': ±1.0°						