

Specifications:

Material And Finish:

Insulator:PA6T,UL94V-0,Color:Natural

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:3.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+125°C

Electrical:

Contact resistance:10m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:800V AC/Minute

Ordering Information

A2005RA-XXQ-01-NG

1 2 3 4 5








1:— Series No.

2:— RA:Deep 90° type

3:— No. of Positions

4:— Q: Tin Plated

5:— G: W/0 Cap In Tape&Reel



RECOMMEND PCB LAYOUT

Circuits	Dimensions		
	A	B	C
02	--	8.00	0.78
03	4.00	10.00	1.20
04	6.00	12.00	1.50
05	8.00	14.00	1.50
06	10.00	16.00	1.50
07	12.00	18.00	1.50
08	14.00	20.00	1.50
09	16.00	22.00	1.50
10	18.00	24.00	7.60
11	20.00	26.00	7.60
12	22.00	28.00	7.60

DR.BY.: Zolin	GENERAL TOLERANCE:		PART NO : A2005RA-XXQ-01-NG	
	LINEAR	ANGLES	DWG. NO.:	
CHKD.: Ren	x.: ±	x': ±6.0°	TITLE :	
	x.x: ±0.25	x.x': ±2.0°	2.0mm Pitch Wafer R/A Deep Type	
APPD.: Billy	x.xx: ±0.15	x.xx': ±	DATE: 09-Jul-2024	
	x.xxx: ±0.08	x.xxx': ±		

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1

SCALE: 1:1

UNIT: mm



THIRD ANGLE PROJECTION

A4

1X	ORIGINAL	Zolin	
REV.	DESCRIPTION	DR.BY	ECN. NO