

Specifications:**Material And Finish:**

Insulator:PBT UL94V-0 Color:Red

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:10.0 Amp (16AWG)

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:10m Ohm Max

Insulator resistance:100M ohm min.

Withstanding Voltage:1000V AC/Minute

Ordering InformationA400005R-35X-02-C
1 2 3 4 5

- 1: — Series No.
2: — R:R/A Type
3: — No. of Positions
4: — A:Gold Flash




F:20u" Gold on Contact;Gold Flash on all

G:20u" Gold on Contact;Matte Tin on tail


H:Gold Flash on Contact;Matte Tin on tail

S:Matte Tin Plated

- 5: — C:In Tray



Recommended PCB Layout



SEC A-A

5X			
4X			
3X			
2X	Deng	20230421	
1X	ORIGINAL	Kenry	
REV.	DESCRIPTION	DR.BY	ECN. NO.


DR.BY.: Kenry
CHKD.: Tony
APPD.: Billy

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.30	X': ±5.0°
X.X: ±0.20	X.X': ±3.0°
X.XX: ±0.15	X.XX': ±2.0°
X.XXX: ±0.10	X.XXX': ±1.0°

PART NO : A400005R-35X-02-C
DWG. NO.:
TITLE : 4.00mm Pitch Header Assembly, R/A Type
DATE: 19-Jan-2015

HJBRIGHT® 东莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm



THIRD ANGLE PROJECTION

A4