

A4

Specifications:
Material And Finish:
Insulator:LCP UL94V-0 Color:Black
Contact:High contactivity copper alloy
Plated:See Ordering Information

Rating:
Current Rating:23Amp AC/DC(12AWG/Per pin)
Voltage Rating:600V AC/DC
Operating Temperature Range:-40~+105°C

Electrical:
Contact resistance:10m Ohm Max
Insulator resistance:1000M ohm min.
Withstanding Voltage:2200V AC/Minute

Ordering Information

A57001S-XXS-01-XX

1 2 3 4 5 6


- 1: — Series No.
2: — S: Straight Type
3: — No. of Positions
4: — S: Matte tin Plated
5: — A: A Type
B: B Type
6: — A: In Bag
B: In Tube
C: In Tray

Poles	Dimensions (mm)				
	A	B	C	D	E
02P		6.35	10.34	7.70	6.17
04P	5.70	12.05	16.04	6.70	5.17
06P	11.40	17.75	21.74		
08P	17.10	23.45	27.44		
10P	22.80	29.15	33.14		
12P	28.50	34.85	38.84		

5X				DR.BY.:	
4X				Sophia	
3X	Update code options	Judyyan	20220811	CHKD.:	
2X	Increase the mode of packaging	Mark	2021-06-17	Tony	
1X	ORIGINAL	Sophia		APPD.:	
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	


GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.30	X': ±5.0°
X.X: ±0.20	X.X': ±3.0°
X.XX: ±0.15	X.XX': ±2.0°
X.XXX: ±0.10	X.XXX': ±1.0°

PART NO : A57001S-XXS-01-XX
DWG. NO.:
TITLE : 5.7Wafer 2*XP DIP STRAIGHT LCP
DATE: 17-Dec-2020


HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
SHEET: 2/2		A4
SCALE: 1:1		
UNIT: mm		
THIRD ANGLE PROJECTION		

A Type


2 CKTS




12 CKTS



4 CKTS



10 CKTS



6 CKTS




8 CKTS



B Type


2 CKTS




12 CKTS




4 CKTS



10 CKTS



6 CKTS



8 CKTS

