

Specifications:

Material And Finish:

Insulator:Nylon66 UL94V-0 Color:Natural

Rating:

Current Rating:3.0 Amp(22AWG)

Voltage Rating:250V AC/DC


Operating Temperature Range:-40°C~+105°C

Electrical:

Contact resistance:10m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:800V AC/Minute




Ordering Information

H20042-XXP-01-XA

1 2 3 4

- 1: — Series No.
2: — No. of Positions
3: — N:Natural
B:Black
4: — A:In Bag



Poles	Dimensions (mm)	
	A	B
04P	2.00	4.54
06P	4.00	6.54
08P	6.00	8.54
10P	8.00	10.70
12P	10.00	12.70
14P	12.00	14.70
16P	14.00	16.70
18P	16.00	18.70
20P	18.00	20.70
22P	20.00	22.70
24P	22.00	24.70
26P	24.00	26.70
28P	26.00	28.70
30P	28.00	30.70
32P	30.00	32.70
34P	32.00	34.70
36P	34.00	36.70
38P	36.00	38.70
40P	38.00	40.70

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : H20042-XXP-01-XA	
4X				Samson	LINEAR	ANGLES	DWG. NO.:	
3X				CHKD.:	X.:	X': ±5.0°	TITLE :	
2X	Update code options	Judyyan	20221125	Tony	X.X: ±0.30	X.X': ±3.0°	2.00mm Crimp Style Connectors	
1X	ORIGINAL	Samson		APPD.:	X.XX: ±0.20	X.XX': ±2.0°	DATE: 23-Oct-2017	
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	X.XXX: ±0.10	X.XXX': ±1.0°	UNIT: mm	

HJBRIGHT®


東莞市華晶電子有限公司

BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1

SCALE: 1:1

UNIT: mm



THIRD ANGLE PROJECTION

A4