

RoHS Compliant

Specifications:
 Material And Finish:
 Insulator:
 Contact:Copper alloy
 Plated:See Ordering Information
 Wire Range:AWG#18~#24

Rating:
 Current Rating:5.0 Amp
 Voltage Rating:250V AC/DC
 Operating Temperature
 Range:-40~+105°C

Electrical:
 Contact resistance:20m Ohm Max
 Insulator resistance:1000M ohm min.
 Withstanding Voltage:1500V AC/Minute

Ordering Information
 H25080T-PX-01
 1 2 3

1: Series No.
 2: T:Terminal
 3: A:Gold flash
 Q: Tin Plated
 S:Matte Tin Plated

SLICE:C-C

SLICE:A-A

SLICE:B-B

5X				DR.BY.: Deng	GENERAL TOLERANCE:		PART NO : H25080T-PX-01
4X					LINEAR	ANGLES	
3X				CHKD.: Aren	±0.40	±3.0°	TITLE : 2.5mm Pitch Housing Terminal
2X					x.x: ±0.30	x.x°: ±3.0°	
1X	ORIGINAL	Deng		APPD.: Billy	x.xx: ±0.20	x.xx°: ±2.0°	
REV	DESCRIPTION	DR.BY	ECN. NO.		x.xxx: ±0.15	x.xxx°: ±1.0°	