

RoHS Compliant

Specifications:

Material And Finish:

Insulator: PBT UL94V-0 Color: Black

Plated: See Ordering Information

Rating:

Current Rating: 3.0 Amp (20AWG)

Voltage Rating: 12V AC/DC

Operating Temperature Range: $-40^{\circ}\sim+105^{\circ}\text{C}$

Electrical:

Contact resistance: 10m Ohm Max

Insulator resistance: 100M Ohm min.

Dielectric Voltage: 1000V AC/Minute

Ordering Information







H25120-26P-A


1 2 3

1: — Series No.

2: — No. of Positions

3: — A: In Bag



5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : H25120-26P-A	HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Samson	LINEAR	ANGLES	DWG. NO.:			
3X	Update technical parameters	Deng	20230530	CHKD.:	x.:	x': ±5.0°	TITLE : 2.50*4.40mm Pitch Housing	SHEET: 1/1		A4
2X	Update Code options	Judyyan	20221217	Tony	x.x: ±0.30	x.x': ±3.0°		SCALE: 1:1		
1X	ORIGINAL	Tsw		APPD.:	x.xx: ±0.20	x.xx': ±2.0°		UNIT: mm		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 26-Oct-2021			