

Specifications:

Material And Finish:

Insulator:Nylon 66 UL94V-0;Color: Black

Rating:

Current Rating:23A AC/DC (12AWG/Per pin)

Voltage Rating:600V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:10m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:2200V AC/Minute

Ordering Information



H57001-XXP-A

1 2 3


1: — Series No.

2: — No. of Positions


3: — A:In bag




2 CKTS






8 CKTS






4 CKTS



6 CKTS




10 CKTS



BORTTOM RIBS ON 2 CKT ONLY

12 CKTS



Part No.	Dimension mm	
	A	B
02P		8.35
04P	5.70	12.05
06P	11.40	17.75
8P	17.10	23.45
10P	22.80	29.15
12P	28.50	34.85

5X			
4X			
3X			
2X	Update code options	Judyyan	20220728
1X	ORIGINAL	Ken	
REV.	DESCRIPTION	DR.BY	ECN. NO.


DR.BY.: Ken
CHKD.: Mark
APPD.: Billy

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.50	X': ±5.0°
X.X: ±0.40	X.X': ±3.0°
X.XX: ±0.25	X.XX': ±2.0°
X.XXX: ±0.15	X.XXX': ±1.0°

PART NO : H57001-XXP-A
DWG. NO.:
TITLE : 5.7mm Crimping Male Housing
DATE: 16-Jun-2019

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm



THIRD ANGLE PROJECTION

A4