

Specifications:

Material And Finish:

Insulator:PA46 UL94V-0

Contact:Copper alloy

Rating:

Current Rating:9.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+150°C





Electrical:

Contact resistance:5m Ohm Max

Insulator resistance:100M ohm min.

with opening cable guide mounted
(state at time of supply)

contact marking



cable guide pressed on

Ordering Information

M1270-05X-XX-BA

1 2 3 4 5 6

1: — Series No.

2: — No. of Positions

3: — Q: Tin Plated

S: Matte Tin Plated

H: Gold flash on contact;

Matte Tin on tail

4: — 01:A Type Red

02:B Type Green


03:C Type Blue

04:D Type Black


5: — B: 180 Degree

6: — A: In Bag


A Type Red




B Type Green



C Type Blue



D Type Black



5X			
4X			
3X			
2X	Correction of operating temperature	Judyyan	20240305
1X	ORIGINAL	Judyyan	
REV.	DESCRIPTION	DR.BY	ECN. NO.

DR.BY:
JudyyanCHKD.:
ArenAPPD.:
Billy

GENERAL TOLERANCE:

LINEAR

ANGLES

X.: ±0.30 X': ±5.0°

X.X: ±0.20 X.X': ±3.0°

X.XX: ±0.10 X.XX': ±2.0°

X.XXX: ±0.10 X.XXX': ±1.0°

PART NO : M1270-05X-XX-BA

DWG. NO.:

TITLE : MicroBridge Female cable Outlet
180 IDC Type 0.35MM2


DATE: 12-Nov-2021

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1

SCALE: 1:1

UNIT: mm



THIRD ANGLE PROJECTION

A4